

自動門感應器 性能比較表		平移門						90度開關門		工業用門	
		主動及安全複合型						防夾安全開關型		主動及安全複合型	
		NEW 3H-IR14TS	3H-CH01	HR100-CT	HR100	3H-IR14	SSR-3	HR400	HTP-20	SSS-5	KABUTO
檢出方式	紅外線	●	●	●	●	●	●		●	●	●
	超音波										
	無線開關										
	光電							●			
	雷達						●			●	
功能	門扇路徑的監控			●			●				●
	高密度檢知範圍								●		●
	廣域										●
	高位置							4.0m (13.12ft) Max		6.5m (21.3ft) Max	4.7m (15.42ft) Max
	靜止物體檢知	●	●	●	●	●	●	●	●	●	●
	全彩LED	●		●		●		●			●
	平整			●		●					●
	ECO模式	●		●			●			●	●
	降雪模式	●	●	●	●	●	●			●	●
	自我診斷	●	●	●	●	●	●	●	●	●	●
	防水	●		●	●		●		●	●	●
	方向檢知			●			●			●	●
	反射·透過	反射							●		
透過								●			
用途	起動+安全	●	●	●	●	●	●			●	●
	起動										
	安全							●	●		
安裝場所	大型商業設施			●	●		●		●		
	小型商店	●	●	●	●	●	●	●			
	交通設施	●		●	●	●	●		●		
	醫療設施	●		●	●	●	●	●			
	公共設施	●		●	●	●	●				
	環境設施								●		●
	教育機構							●			
	餐飲服務設施	●	●	●	●	●	●				
	工廠設施								●	●	●
	藝文設施	●		●	●	●	●	●			
	辦公大樓	●	●	●	●	●	●	●			●
	休閒設施	●		●	●	●	●	●			●
	住宅	●		●	●	●	●	●			